BSY 4000X





Mainframe Chassis

Axles

Engine Brand Type Power

Crawler Drive System

Crawler drive system Crawler chassis Crawler width Crawler chain

Controls and comfort

Cabin Crawler Control Control Panel Laser / GPS system

Plow mechanism

Plow type Pivot frame Weight compensation Trench depth Trench width

Dimensions

Length Width Height Weight

: Heavy duty welded and reinforced frame : Fixed axles

: Caterpillar : C13 ATAAC : 310 kW / 415 bhp

- : Hydrostatic drive : Oscillating on axles
- : 800 mm bull type
- : D7
-
- : Comfortable operator's cab : Independent
- : Motor Management Information System
- : Prepared

: Semi parallelogram
: Horizontal plane movement L/R
: Variable pressure
: 1800 mm
: 250 mm

: 12.950 mm : 3.200 mm : 3.200 mm : 30.000 kg





Barth Hollanddrain P.O. Box 5150 3295 ZH 's-Gravendeel The Netherlands



Tel.: +31(0)78 673 33 00 Fax: +31 (0)78 673 47 00 E: info@barthhollanddrain.nl W: www.barthhollanddrain.nl

BSY 4000X



Safety


- Platform with railing
- Emergency stops outside/inside
- Working lights
- Anti-slip tape

Options

- Cummins or Scania Diesel engine
- Side tilt integrated in chassis
- Double Linkage System
- Dual Path Control
 (1 Multifunctional Joystick for track drive)
- Air Conditioning
- Laser or GPS system
- Country Specific Package Deals







The company

Barth Hollanddrain is specialized in design, development, manufacturing, marketing, sales and service of a wide range of heavy duty Drainage, Dewatering and Trenching machines. Plows and complementary equipment like Gravel Trailers or Flushing Machines as well as spare parts for the subsurface cable and dewatering pipe laying industry are part of an extensive product range; the widest program in the drainage industry. The majority of customers have their core business in agricultural, irrigation, recreational, utility, construction and adjacent industries. Machines operate in target markets in Europe, Middle East, Africa, Far East, United States and South America. Hollanddrain machines are designed to be used in extreme subsurface conditions up to easily 8 meter or more in different types of soil. Hollanddrain assures a favorable total cost of ownership due to extremely low operating cost and durable design.

Barth Hollanddrain P.O. Box 5150 3295 ZH 's-Gravendeel The Netherlands



Tel.: +31(0)78 673 33 00 Fax: +31 (0)78 673 47 00 E: info@barthhollanddrain.nl W: www.barthhollanddrain.nl